

# HEAVY DUTY AND SPECIAL SHUTTLELESS AUTOMATIC LOOMS

	TRX 160	TRX 160-E	TRX 320	TRX 320-E	TRX 600-E		TM 130	TM 230	TRXA 180	TRXA 180-E	TRXA 360	TRXA 360-E
Selvage binding	Bobbin	Bobbin	Bobbin	Bobbin	Bobbin		Latch Needle	Latch Needle	Latch Needle	Latch Needle	Latch Needle	Latch Needle
Spaces	2	2	1	1	1		2	1	2	2	1	1
Reed width mms.	160	160	330	330	620		130	230	180	180	370	370
Shafts (max.)	14	16	14	16	16		14	12	14	16	14	16
Shed formation	Positive cams	Electronic Dobby	Positive cams	Electronic Dobby	Electronic dobby		Negative cams	Negative cams	Positive cams	Electronic Dobby	Positive cams	Electronic dobby
Pick-repeats	1:6/8	endless	1:6/8	endless	endless		1:6/8	1:6/8	1:6/8	endless	1:6/8	endless
Motor power (Kw)	2.6	2.6	2.6	2.6	2.6		2.6	2.6	2.6	2.6	2.6	2.6
Pick density (min-max)	2-40	2-40	2-40	2-40	2-40		2-40	2-40	2-40	2-40	2-40	2-40
Weft feed	Weft accumulator	Weft accumulator	Weft accumulator	Weft accumulator	Weft accumulator		Weft accumulator	Weft accumulator	Weft accumulator	Weft accumulator	Weft accumulator	Weft accumulator
Measures (cms.)	130x225x145	160x225x145	120x225x145	120x225x145	225x290x145		120x160x130	100x160x130	130x225x145	160x225x145	120x225x145	160x225x145
Weight (Kgs)	1100	1500	1100	1500	1800		800	800	1100	1500	1100	1500
Weaving speed (max, r.p.m.)	250	250	200	200	150		700	500	250	250-300	200	200



METAG SRL - Via P. da Volpedo 79-81 - 20092 Cinisello B. (MI) ITALY  
 Tel. +39 02 66049440 - Fax +39 02 6128211 - [www.metag.it](http://www.metag.it) - [info@metag.it](mailto:info@metag.it)

*Mighty* **METAG**

